

Technical data sheet

Lyovapor™ L-250 Basic / L-250 Pro

The Lyovapor™ L-250 Basic / L-250 Pro with EcoStream™ technology offers high freeze drying performance ($-85\text{ }^{\circ}\text{C}$, $\leq 5\text{ kg}$) at low global warming potential and process time optimization by endpoint determination. Infinite Control™ allows easy method creation, data logging, chart recording in real-time and interrupting if needed at anytime - anywhere.



Scope of delivery

All configurations are supplied ready to use.



NOTE

The scope of delivery depends on the configuration of the purchase order.

Accessories are delivered as per the purchase order, order confirmation, and delivery note.

Components

Lyovapor™ L-250

| | |
|---|---|
| Lyovapor™ L-250 Basic or Lyovapor™ L-250 Pro | 1 |
| Power cord | 1 |
| Operation Manual | 1 |
| Technical data sheet | 1 |
| Vacuum clamp, ISO-KF 16 | 1 |
| Vacuum clamps, ISO-KF 25 | 1 |
| O-ring, 300 mm | 1 |
| Vacuum tubing adaptor, ISO-KF 16 to ISO-KF 25 | 1 |
| Pressure sensor PPG011 (incl. seals and clamps) | 1 |

Order code

Choose the configuration according to your needs:

L-250 Basic bundle

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|-------------|
| 1 | 1 | L | 2 | 5 | 0 | I | N | 0 | 0 | 0 | 0 | L-250 Basic |
|---|---|---|---|---|---|---|---|---|---|---|---|-------------|

Vacuum control¹

| | | | | | | | | |
|---|---|---|---|---|---|---|---|-------------------------|
| 1 | 1 | 0 | 8 | 0 | 1 | 6 | 1 | Ultimate vacuum control |
| 1 | 1 | 0 | 8 | 0 | 1 | 6 | 2 | Advanced vacuum control |

Drying chamber¹

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|--|
| 1 | 1 | D | C | I | N | 0 | 1 | 0 | 0 | 0 | Drying rack manifold 12 |
| 1 | 1 | D | C | I | N | 0 | 2 | 0 | 0 | 0 | Drying rack manifold 24 |
| 1 | 1 | D | C | I | N | 1 | 4 | 1 | 0 | 0 | Drying chamber 4 shelves |
| 1 | 1 | D | C | I | N | 1 | 4 | 2 | 0 | 0 | Drying chamber 4 shelves with top cover manifold |
| 1 | 1 | D | C | I | N | 1 | 4 | 3 | 0 | 0 | Drying chamber 4 shelves with stoppering |
| 1 | 1 | D | C | I | N | 1 | 6 | 1 | 0 | 0 | Drying chamber 6 shelves |
| 1 | 1 | D | C | I | N | 1 | 6 | 2 | 0 | 0 | Drying chamber 6 shelves with top cover manifold |

Optional

| | | | | | | | | |
|---|---|---|---|---|---|---|---|----------------------------------|
| 1 | 1 | 0 | 6 | 5 | 6 | 5 | 2 | Vacuum pump Pfeiffer Duo 6 |
| 1 | 1 | 0 | 6 | 8 | 1 | 5 | 8 | Vacuum pump Edwards nXDS6iC |
| 1 | 1 | 0 | 8 | 0 | 4 | 4 | 0 | Trolley L-250 |
| 1 | 1 | 0 | 7 | 6 | 7 | 2 | 0 | Upgrade Basic to Pro instrument |
| 1 | 1 | 0 | 8 | 0 | 7 | 7 | 0 | Set for pressure difference test |

¹ Selection of one option is required

L-250 Pro bundle

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|-----------|
| 1 | 1 | L | 2 | 5 | 0 | P | H | 0 | 0 | 0 | 0 | L-250 Pro |
|---|---|---|---|---|---|---|---|---|---|---|---|-----------|

Vacuum control¹

| | | | | | | | | |
|---|---|---|---|---|---|---|---|-------------------------|
| 1 | 1 | 0 | 8 | 0 | 1 | 6 | 2 | Advanced vacuum control |
|---|---|---|---|---|---|---|---|-------------------------|

Drying chamber¹

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 1 | D | C | I | N | 0 | 1 | 0 | 0 | 0 | Drying rack manifold 12 |
| 1 | 1 | D | C | P | H | 2 | 4 | 1 | 0 | 0 | Drying chamber 4 heatable shelves |
| 1 | 1 | D | C | P | H | 2 | 4 | 1 | 0 | 1 | Drying chamber 4 heatable shelves with pressure difference test |
| 1 | 1 | D | C | P | H | 2 | 4 | 2 | 0 | 0 | Drying chamber 4 heatable shelves with top cover manifold |
| 1 | 1 | D | C | P | H | 2 | 4 | 3 | 0 | 0 | Drying chamber 4 heatable shelves with stoppering |
| 1 | 1 | D | C | P | H | 2 | 4 | 3 | 0 | 1 | Drying chamber 4 heatable shelves with pressure difference test, stoppering |
| 1 | 1 | D | C | P | H | 2 | 6 | 1 | 0 | 0 | Drying chamber 6 heatable shelves |
| 1 | 1 | D | C | P | H | 2 | 6 | 1 | 0 | 1 | Drying chamber 6 heatable shelves with pressure difference test |
| 1 | 1 | D | C | P | H | 2 | 6 | 2 | 0 | 0 | Drying chamber 6 heatable shelves with top cover manifold |

Optional

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 6 | 4 | 0 | 3 | 1 | Sample temperature sensor |
| 1 | 1 | 0 | 6 | 5 | 6 | 6 | 8 | Lyovapor™ software license |
| 1 | 1 | 0 | 6 | 5 | 6 | 5 | 2 | Vacuum pump Pfeiffer Duo 6 |
| 1 | 1 | 0 | 6 | 8 | 1 | 5 | 8 | Vacuum pump Edwards nXDS6iC |
| 1 | 1 | 0 | 8 | 0 | 4 | 4 | 0 | Trolley L-250 |
| 1 | 1 | 0 | 8 | 0 | 7 | 7 | 0 | Set for pressure difference test for manifold application |

¹ Selection of one option is required

Technical data

Lyovapor™ L-250 Basic/L-250 Pro

| Specification | L-250 Basic | L-250 Pro |
|---|----------------------|----------------------|
| Dimensions without drying attachments (W x D x H) | 503 x 645 x 511 mm | 503 x 645 x 511 mm |
| Weight | 65.6 kg | 67.4 kg |
| Minimum clearance on all sides | 300 mm | 300 mm |
| Minimum space requirements | 503 x 645 x 510 mm | 503 x 645 x 510 mm |
| Connection voltage | 200 – 240 VAC ±10% | 200 – 240 VAC ±10% |
| Rated power consumption | 1300 VA | 1400 VA |
| Max. power consumption | 1800 VA | 1800 VA |
| Fuse | 10 A | 10 A |
| Frequency | 50/60 Hz | 50/60 Hz |
| Overvoltage category | II | II |
| Protection rating | IP20 | IP20 |
| Pollution degree | 2 | 2 |
| Condensing capacity | 4 kg/24 h | 4 kg/24 h |
| Lowest condenser temperature | -85 °C | -85 °C |
| Temperature divergence | ±1.0 °C | ±1.0 °C |
| Condenser capacity | ≤ 5 kg | ≤ 5 kg |
| Condenser surface area | 1524 cm ² | 1524 cm ² |
| Compressor cooling capacity at -10 °C ambient temperature | 1.5 kW | 1.5 kW |
| Refrigerants | R290, R600, R1150 | R290, R600, R1150 |
| Refrigerant quantity | < 100 g | < 100 g |
| Vacuum generation time to 0.1 mbar | Typically ≤ 10 min | Typically ≤ 10 min |
| Volume-based leakage rate | < 10 mbar L/h | < 10 mbar L/h |
| Lowest system vacuum | 0.03 mbar | 0.03 mbar |
| Control range vacuum | 0.1 – 1 mbar | 0.1 – 1 mbar |
| Shelf heating | max. 60 °C | max. 60 °C |
| Shelf temperature control tolerance | ±1.0 °C | ±1.0 °C |
| Certificates | CE/CSA | CE/CSA |
| Drying attachments operating height | 1100 mm | 1100 mm |
| Noise level | < 68 dB | < 68 dB |
| Inert gas connection (relative) | 0.5 bar | 0.5 bar |

Ambient conditions

For indoor use only.

| | |
|-------------------------------|-----------------------------------|
| Max. altitude above sea level | 2'000 m |
| Ambient temperature | 5 - 30 °C ¹ |
| Maximum relative humidity | 80 % for temperatures up to 30 °C |
| Storage temperature | max. 70 °C |

¹ Above 30°C the ice condenser power decreases. Reduce sample quantity to prevent sample collapse.

Drying chamber bundles

| Drying rack manifold | Order no. |
|--|-------------|
| Drying rack manifold 12 with 12 manifold valves and baseplate | 11DCIN01000 |
| Drying rack manifold 24 with 24 manifold valves and baseplate | 11DCIN02000 |

| Drying chamber non-heatable shelves | Order no. |
|--|-------------|
| Drying chamber 4 shelves with top cover, support ring and 4 non-heatable shelves | 11DCIN14100 |
| Drying chamber manifold, 4 shelves with top cover manifold, support ring, 4 non-heatable shelves and 12 manifold valves | 11DCIN14200 |
| Drying chamber with stoppering cover, support ring and non-heatable shelves | 11DCIN14300 |
| Drying chamber 6 shelves with top cover, support ring and 6 non-heatable shelves | 11DCIN16100 |
| Drying chamber manifold, 6 shelves with top cover manifold, support ring, 6 non-heatable shelves and 12 manifold valves | 11DCIN16200 |

| Drying chamber heatable shelves | Order no. |
|---|-------------|
| Drying chamber 4 heatable shelves with top cover | 11DCPH24100 |
| Drying chamber 4 heatable shelves with top cover and pressure difference test | 11DCPH24101 |
| Drying chamber 4 heatable shelves with top cover manifold and 4 heatable shelves | 11DCPH24200 |
| Drying chamber 4 heatable shelves with stoppering cover and 4 heatable shelves | 11DCPH24300 |
| Drying chamber 4 heatable shelves with stoppering cover, 4 heatable shelves and pressure difference test | 11DCPH24301 |
| Drying chamber 6 heatable shelves with top cover and 6 heatable shelves | 11DCPH26100 |

| Drying chamber heatable shelves | Order no. |
|--|-------------|
| Drying chamber 6 heatable shelves with top cover, 6 heatable shelves and pressure difference test | 11DCPH26101 |
| Drying chamber 6 heatable shelves with top cover manifold and 6 heatable shelves | 11DCPH26200 |

Spare parts and accessories







Use only genuine BUCHI consumables and spare parts in order to ensure correct, safe and reliable operation of the system.









NOTE



Any modifications of spare parts or assemblies are only allowed with the prior written permission of BUCHI.










Accessories










| | Order no. | Image |
|--|-----------|---|
| Main valve | 11076675 |  |
| Pressure regulation valve | 11076679 |  |
| Aeration valve | 11064724 |  |
| Pirani / Piezo pressure sensor | 11062228 |  |
| Capacitive pressure sensor Inficon CDG 020 D | 11062230 |  |
| PT1000 sample temperature sensor | 11064031 |  |










| | Order no. | Image |
|--|-----------|---|
| Set for pressure difference test incl. extension cable for PPG011 and CDG 020D sensors, PMMA top cover, seals and clamps | 11067590 |  |
| Set for pressure difference test incl. extension cable of PPG011 and CDG 020D sensors, stoppering top cover, seals and clamps | 11070102 |  |
| Set for pressure difference test Only for manifold rack steel with 12 connections | 11080770 |  |
| Trolley L-250, stainless steel coated | 11080440 |  |
| SD-Card 1 GB | 11064730 |  |
| Connection cable, for vacuum pump | 11064934 |  |


Top-mount drying rack accessories

| | Order no. | Image |
|--|-----------|---|
| Drying chamber tube, PMMA, for 4 shelves L 368 mm, Ø 300 mm | 11063278 |  |
| Drying chamber tube, PMMA, for 6 shelves L 480 mm, Ø 300 mm | 11065093 |  |








| | Order no. | Image |
|---|-----------|---|
| Top cover, PMMA, without sealing Ø 300 mm, H 50 mm | 11062912 |  |
| Top cover manifold, PMMA, with 12 valves, without sealing Ø 300 mm, W 546 mm, H 127 mm | 11065595 |  |
| Top cover stoppering, without sealing only for rack for 4 heatable shelves Ø 300 mm, H 330 mm, W 320 mm | 11064314 |  |
| Rack for 4 heatable shelves H 356 mm, Ø 265 mm , shelf distance 30-75 mm | 11065102 |  |
| Rack for 6 heatable shelves H 468 mm, Ø 265 mm, shelf distance 30-75 mm | 11065103 |  |
| Heatable shelf, aluminum coated, with connection cable Ø 219.5 mm, surface area 376 cm ² | 11064095 |  |
| Sample tray, stainless steel Ø 220 mm, H 18.5 mm | 11061439 |  |
| Ferrule, Ø 218 mm, H 40 mm | 11065816 |  |
| Drying rack manifold, stainless steel, with 12 valves H 340 mm, W 777 mm | 11063664 |  |





| | Order no. | Image |
|--|-----------|---|
| Drip pan, for manifold | 11066358 |  |
| Support for rack, stainless steel H 4 mm | 11063789 |  |
| Baseplate, stainless steel, for manifold rack | 11064953 |  |
| Baseplate, PMMA, for manifold rack | 11065733 |  |
| Suction nipple For manifold application to create vacuum in sample flasks | 11065819 |  |
| Ampoule adapter for manifold with 19 ampoule connections and cap adapter | 11065725 |  |
| Manifold valve, EPDM/Silicone, with SJ 29/32 | 11062300 |  |
| Flask beaker for manifold 100 mL with cap adapter and integrated filter | 11066140 |  |
| Flask beaker for manifold 200 mL with cap adapter and integrated filter | 11066141 |  |

| | Order no. | Image |
|--|-----------|---|
| Flask beaker for manifold 800 mL with cap adapter and integrated filter | 11069474 |  |
| Flask beaker for manifold 1200 mL with cap adapter and integrated filter | 11066143 |  |
| Manifold flask adapter set with 12 adapters, incl. filter paper | 11066144 |  |
| Manifold flask adapter set with 6 adapters, incl. filter paper | 11067334 |  |
| Manifold flask adapter set, 24/40 joint size with 12 adapters, incl. filter paper | 11066171 |  |
| Manifold flask adapter set, 24/40 joint size with 6 adapters, incl. filter paper | 11067333 |  |
| Filter round 20mm Set à 100pcs Filter for manifold valve | 11065801 |  |
| Filter round 47mm Set à 100pcs Beaker flasks with volume above 600 mL | 11065731 |  |
| Filter round 30mm Set à 100pcs Beaker flasks with volume below 600 mL | 11065728 |  |

| | Order no. | Image |
|---------------------------------|-----------|---|
| Unheatable shelf for stoppering | 11079991 |  |

Spare parts

| | Order no. | Image |
|-------------------------------|-----------|---|
| Pro user interface | 11081893 |  |
| O-Ring Ø 300 mm | 11065367 |  |
| Vacuum hose, KF 25, L 1000 mm | 11066031 |  |
| Vacuum clamp KF 16 | 11064939 |  |
| Vacuum seal KF 16 | 11063455 |  |
| Vacuum seal KF 25 | 11063457 |  |
| Vacuum seal KF 40 | 11063659 |  |

| | Order no. | Image |
|--|-----------|---|
| Vacuum flange adapter, stainless steel, KF 16 to KF 25 | 11064870 |  |
| Blind flange KF 16 | 11064902 |  |
| Blind flange KF 25 | 11063660 |  |
| Blind flange KF 40 | 11063661 |  |
| Vacuum pump Pfeiffer Duo 6 | 11065652 | |
| Vacuum pump Edwards nXDS6iC | 11068158 | |

Software

| | Order no. |
|----------------------------|-----------|
| Lyovapor™ software USB | 11065667 |
| Lyovapor™ software licence | 11065668 |

IQ/OQ kits

| | Order no. |
|-----------------------|-----------|
| IQ/OQ set L-250 en | 11081555 |
| Repeating OQ L-250 en | 11081556 |

Maintenance kits

| | Order no. |
|---|-----------|
| Customer kit for L-250, with advanced vacuum control | 11076718 |
| Frequently used wear and spare parts for self-servicing your device, conveniently gathered in one kit | |
| Customer kit for L-250, with ultimate vacuum control | 11076719 |
| Frequently used wear and spare parts for self-servicing your device, conveniently gathered in one kit | |



11594484A en Lyovapor™ L-250 Basic / L-250 Pro 05.2024
Technical data are subject to change without notice
Quality Systems ISO 9001

We are represented by more than 100 distribution partners worldwide.
Find your local representative at:

www.buchi.com

Quality in your hands
